

Program LEQ Professional v. 6-2016 dla Windows

Projekt:
D:\PROJEKTY HAŁAS\Barter ROS\hałas dzień.dat

Dane do obliczeń :

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
1	649.6	285.6	4.0	65.0	WN
2	650.9	284.2	4.0	65.0	WN
3	652.7	283.4	4.0	65.0	WN
4	654.0	281.6	1.0	65.0	WW
5	656.6	279.8	1.0	65.0	WW
6	658.0	278.1	1.0	65.0	WW
7	624.5	284.2	1.0	70.0	Pom
8	622.6	281.3	1.0	70.0	Pom
9	619.7	279.4	1.0	70.0	Pom
10	617.8	276.5	1.0	70.0	Pom
11	613.9	273.6	1.0	70.0	Spr
12	612.0	272.6	1.0	70.0	Spr
13	612.0	271.7	1.0	70.0	Spr
14	608.2	267.8	1.0	70.0	Spr
15	253.9	354.2	1.0	54.7	So
16	278.9	358.1	1.0	54.7	So
17	304.8	375.4	1.0	54.7	So
18	329.8	391.7	1.0	54.7	So
19	368.2	396.5	1.0	54.7	So
20	397.9	397.4	1.0	54.7	So
21	424.8	400.3	1.0	54.7	So
22	444.0	404.2	1.0	54.7	So
23	467.0	408.0	1.0	54.7	So
24	493.9	409.9	1.0	54.7	So
25	516.0	414.7	1.0	54.7	So
26	541.9	417.6	1.0	54.7	So
27	542.9	420.5	1.0	54.7	So
28	566.9	420.5	1.0	54.7	So
29	589.9	422.4	1.0	54.7	So
30	587.0	421.4	1.0	54.7	So
31	612.0	423.4	1.0	54.7	So
32	637.9	433.9	1.0	54.7	So
33	663.8	436.8	1.0	54.7	So
34	685.0	434.9	1.0	54.7	So
35	708.0	430.1	1.0	54.7	So
36	715.7	422.4	1.0	54.7	So
37	731.0	413.8	1.0	54.7	So
38	753.1	407.0	1.0	54.7	So
39	777.1	406.1	1.0	54.7	So
40	803.0	409.0	1.0	54.7	So
41	829.9	400.3	1.0	54.7	So
42	829.9	382.1	1.0	54.7	So
43	824.2	363.8	1.0	54.7	So
44	822.2	345.6	1.0	54.7	So
45	349.9	393.6	1.0	54.7	So
46	291.4	363.8	1.0	54.7	So
47	265.4	354.2	1.0	54.7	So
48	818.4	406.1	1.0	54.7	So
49	480.5	409.0	1.0	54.7	So
50	623.5	426.2	1.0	54.7	So
51	246.2	353.3	1.5	80.2	Sc

52	273.1	356.2	1.5	80.2	Sc
53	281.8	361.0	1.5	80.2	Sc
54	297.1	366.7	1.5	80.2	Sc
55	315.4	381.1	1.5	80.2	Sc
56	321.1	384.0	1.5	80.2	Sc
57	338.4	392.6	1.5	80.2	Sc
58	359.5	393.6	1.5	80.2	Sc
59	379.7	396.5	1.5	80.2	Sc
60	387.4	396.5	1.5	80.2	Sc
61	410.4	398.4	1.5	80.2	Sc
62	454.6	407.0	1.5	80.2	Sc
63	433.4	401.3	1.5	80.2	Sc
64	460.3	407.0	1.5	80.2	Sc
65	473.8	408.0	1.5	80.2	Sc
66	487.2	408.0	1.5	80.2	Sc
67	502.6	410.9	1.5	80.2	Sc
68	525.6	415.7	1.5	80.2	Sc
69	554.4	419.5	1.5	80.2	Sc
70	575.5	421.4	1.5	80.2	Sc
71	598.6	422.4	1.5	80.2	Sc
72	605.3	423.4	1.5	80.2	Sc
73	616.8	425.3	1.5	80.2	Sc
74	649.6	435.2	1.5	80.2	Sc
75	674.0	437.2	1.5	80.2	Sc
76	695.8	434.5	1.5	80.2	Sc
77	723.7	417.5	1.5	80.2	Sc
78	739.3	409.4	1.5	80.2	Sc
79	761.1	406.6	1.5	80.2	Sc
80	788.3	406.6	1.5	80.2	Sc
81	829.8	392.4	1.5	80.2	Sc
82	826.4	373.3	1.5	80.2	Sc
83	823.6	354.3	1.5	80.2	Sc
84	812.6	361.9	1.5	80.2	Sc
85	788.6	361.9	1.5	80.2	Sc
86	773.3	352.3	1.5	80.2	Sc
87	757.9	347.5	1.5	80.2	Sc
88	747.4	340.8	1.5	80.2	Sc
89	732.0	333.1	1.5	80.2	Sc
90	718.6	323.5	1.5	80.2	Sc
91	709.9	308.2	1.5	80.2	Sc
92	699.4	296.6	1.5	80.2	Sc
93	694.6	281.3	1.5	80.2	Sc
94	686.9	269.8	1.5	80.2	Sc
95	679.2	261.1	1.5	80.2	Sc
96	679.2	255.4	1.5	80.2	Sc
97	676.3	241.9	1.5	80.2	Sc
98	671.5	219.8	1.5	80.2	Sc
99	672.5	199.7	1.5	80.2	Sc
100	673.4	182.4	1.5	80.2	Sc
101	673.4	169.0	1.5	80.2	Sc
102	673.4	155.5	1.5	80.2	Sc
103	668.6	276.5	1.5	75.0	Wo
104	659.0	178.6	1.5	75.0	Wo
105	652.3	191.0	1.5	102.0	£
106	653.3	167.0	1.5	102.0	£
107	530.4	234.2	1.5	83.8	Z1
108	537.1	246.7	1.5	83.8	Z1
109	549.6	257.3	1.5	83.8	Z1
110	558.2	272.6	1.5	83.8	Z1
111	572.6	285.1	1.5	83.8	Z1
112	587.0	306.2	1.5	83.8	Z1
113	601.4	318.7	1.5	83.8	Z1
114	610.1	333.1	1.5	83.8	Z1

115	620.6	341.8	1.5	83.8	Z1
116	634.1	355.2	1.5	83.8	Z1
117	649.4	370.6	1.5	83.8	Z1
118	670.6	388.8	1.5	83.8	Z1
119	689.8	402.2	1.5	83.8	Z1
120	709.0	415.7	1.5	83.8	Z1
121	726.2	426.2	1.5	83.8	Z1
122	753.1	438.7	1.5	83.8	Z1
123	775.2	443.5	1.5	83.8	Z1
124	803.0	447.4	1.5	83.8	Z1
125	828.0	455.0	1.5	83.8	Z1
126	860.6	457.0	1.5	83.8	Z1
127	902.9	461.8	1.5	83.8	Z1
128	539.0	235.2	1.5	82.0	Z2
129	544.8	244.8	1.5	82.0	Z2
130	552.5	252.5	1.5	82.0	Z2
131	561.1	261.1	1.5	82.0	Z2
132	567.8	268.8	1.5	82.0	Z2
133	573.6	276.5	1.5	82.0	Z2
134	583.2	283.2	1.5	82.0	Z2
135	592.8	296.6	1.5	82.0	Z2
136	603.4	309.1	1.5	82.0	Z2
137	610.1	318.7	1.5	82.0	Z2
138	623.5	328.3	1.5	82.0	Z2
139	631.2	337.0	1.5	82.0	Z2
140	641.8	349.4	1.5	82.0	Z2
141	653.3	360.0	1.5	82.0	Z2
142	663.8	374.4	1.5	82.0	Z2
143	671.5	383.0	1.5	82.0	Z2
144	688.8	393.6	1.5	82.0	Z2
145	704.2	404.2	1.5	82.0	Z2
146	716.6	410.9	1.5	82.0	Z2
147	728.2	420.5	1.5	82.0	Z2
148	737.8	426.2	1.5	82.0	Z2
149	748.3	430.1	1.5	82.0	Z2
150	759.8	435.8	1.5	82.0	Z2
151	779.0	438.7	1.5	82.0	Z2
152	797.3	445.4	1.5	82.0	Z2
153	812.6	446.4	1.5	82.0	Z2
154	824.2	448.3	1.5	82.0	Z2
155	849.1	452.2	1.5	82.0	Z2
156	875.0	457.0	1.5	82.0	Z2
157	546.7	234.2	1.5	82.0	Z3
158	551.5	242.9	1.5	82.0	Z3
159	560.2	253.4	1.5	82.0	Z3
160	575.5	267.8	1.5	82.0	Z3
161	586.1	278.4	1.5	82.0	Z3
162	601.4	297.6	1.5	82.0	Z3
163	613.9	311.0	1.5	82.0	Z3
164	635.0	329.3	1.5	82.0	Z3
165	649.4	349.4	1.5	82.0	Z3
166	668.6	362.9	1.5	82.0	Z3
167	685.0	370.6	1.5	82.0	Z3
168	701.3	378.2	1.5	82.0	Z3
169	718.6	388.8	1.5	82.0	Z3
170	735.8	394.6	1.5	82.0	Z3
171	755.0	395.5	1.5	82.0	Z3
172	768.5	397.4	1.5	82.0	Z3
173	787.7	397.4	1.5	82.0	Z3
174	816.5	390.7	1.5	82.0	Z3
175	560.2	235.2	1.5	82.0	Z4
176	569.8	248.6	1.5	82.0	Z4
177	578.4	258.2	1.5	82.0	Z4

178	588.0	268.8	1.5	82.0	Z4
179	597.6	282.2	1.5	82.0	Z4
180	613.0	297.6	1.5	82.0	Z4
181	627.4	306.2	1.5	82.0	Z4
182	637.9	322.6	1.5	82.0	Z4
183	652.3	335.0	1.5	82.0	Z4
184	667.7	346.6	1.5	82.0	Z4
185	685.0	358.1	1.5	82.0	Z4
186	697.4	367.7	1.5	82.0	Z4
187	719.5	377.3	1.5	82.0	Z4
188	745.4	382.1	1.5	82.0	Z4
189	767.5	383.0	1.5	82.0	Z4
190	784.8	381.1	1.5	82.0	Z4
191	800.2	380.2	1.5	82.0	Z4
192	820.3	377.3	1.5	82.0	Z4
193	842.4	372.5	1.5	82.0	Z4
194	854.9	369.6	1.5	82.0	Z4
195	869.3	366.7	1.5	82.0	Z4

=====

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
1	646.1	285.1	656.6	295.7	670.1	284.2	658.6	274.6	0.0	4.0

=====

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
1	sc.1 L wew	88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.2	L wew	93.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.3	L wew	86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
sc.4	L wew	88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R sc	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
dach	L wew	92.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
	R d	40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

=====